

Hauptsitz

Gloor Pumpenbau AG
Thunstrasse 25 | CH-3113 Rubigen
Tel. +41 (0)31 721 52 24
Fax +41 (0)31 721 54 34
info@gloor-pumpen.ch
www.gloor-pumpen.ch

Filiale Mittelland

Gloor Pumpenbau AG
Industriestrasse 25
CH-5036 Oberentfelden
Tel. +41 (0)62 552 02 08
info@gloor-pumpen.ch
www.gloor-pumpen.ch

Filiale Suisse Romande

Gloor Pumpenbau SA
Rue du Collège 3 | Case postale
CH-1410 Thierrens
Tél. +41 (0)21 905 10 80
info@gloor-pumpen.ch
www.gloor-pumpen.ch

GHV Series

Variable speed sets equipped with Hydrovar® frequency converter and two multistage vertical pumps.

Specifications

Number of pumps: from 2
Delivery: up to 28 m³/h
Head: up to 160 m
Input voltage of panel:
1 x 230 V 50 Hz (single-phase)
3 x 400 V 50 Hz (three-phase)
Power range:
2 x 2,2 kW (single-phase)
2 x 4 kW (three-phase)
Motor starting via variable frequency operation
Water temperature of the liquid: 0°C to +80°C
Pump type: vertical e-SV™ series

Materials

Pump: Stainless steel
Manifold: AISI 304 stainless steel

Product applications and characteristics

Easy to install

Trouble-free servicing

Pressure transducer controlled

Compact solution

Constant output pressure

Variable speed motors with consequently reduced noise

Protection against dry running

Accessories: Hydro tube

Versions with non-return valve on suction line available on request

For hydraulic performances of 3 and 4 pumps boosters please check our technical catalogue

Special configurations available on request

